PATENT ABSTRACTS OF JAPAN

(11)Publication number:

2000-173766

(43)Date of publication of application: 23.06.2000

(51)Int.CI.

H05B 33/04 G09F 9/30 H05B 33/14 H05B 33/26

(21)Application number: 11-277089

(71)Applicant : SANYO ELECTRIC GO LTD

(22)Date of filing:

29.09.1999

(72)Inventor: YAMADA TSUTOMU

FURUMIYA NAOAKI

(30)Priority

Priority number: 10277997

Priority date: 30.09.1998


Priority country: JP

(54) DISPLAY DEVICE

(57)Abstract:

PROBLEM TO BE SOLVED: To provide a display device that can prevent display degradation due to moisture and can be designed, without being restricted on the size and capability of TFTs for driving a luminescent layer in relation to the display device, wherein a luminescent layer emitting light in itself like an organic EL layer is enclosed inside.

SOLUTION: A first board 1 is bonded to a cap 10, and a powdery desiccant is mixed in a seal 11 for sealing a display region. Moisture permeation from board surfaces nipping the display region can nearly be neglected, and since the moisture permeating the seal 11 is adsorbed by the desiccant, a luminescent layer can be prevented from being degraded by the moisture. The display region is protected from the moisture by covering the display region with a resin sealing layer formed of a desiccantmixed resin. The moisture is surely adsorbed by forming a slot on the board and by arranging the desiccant in it.



LEGAL STATUS

[Date of request for examination]

01.07.2003

[Date of sending the examiner's decision of

rejection

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision

2/2 ページ

of rejection]
[Date of requesting appeal against examiner's decision of rejection]
[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office